

Pumping Flow Tees

- Ductile Iron construction.
- Zinc phosphate coated for better thread lubrication.
- Most precise alignment in the industry.
- Hundreds of thread combinations.
- 2" & 2-1/2" forged steel tees and 3" cast steel tees available.
- Corrosion resistant coatings available.
- 4-way cross configuration available in 2" LP.
- 1" NPT standard (or smaller) bleeder port. 2" available in some sizes (bleeder port can be left blank by request).



3000 PSI WP

**Most Common Models (Other Models Available)
3000 PSI Working Pressure Heavy Duty Tees**

Model No.	Bottom Thread (Tubing or LP)	Top Thread (Tubing or LP)	Major Side Outlet (LP)	Height	Weight
CT-7	2"	2"	2"	6"	9 lbs.
CT-13	2" Male	2"	2"	7-1/4"	7 lbs.
CT-8	2"	2-1/2"	2"	7-1/4"	13 lbs.
CT-17	2"	3"	2"	8"	21 lbs.
CT-1	2"	3"	3"	8"	18 lbs.
CT-18	2-1/2"	2"	2"	7-1/4"	13 lbs.
CT-11	2-1/2"	2-1/2"	2"	7-1/4"	13 lbs.
CT-14	2-1/2" Male	2-1/2"	2"-2-1/2"	8"	10 lbs.
CT-9	2-1/2"	2-1/2"	2-1/2"	7-1/4"	12 lbs.
CT-19	2-1/2"	2-1/2"	3"	8"	20 lbs.
CT-12	2-1/2"	3"	2"	8"	20 lbs.
CT-10	2-1/2"	3"	2-1/2"	8"	20 lbs.
CT-16	2-1/2" Male	3"	2"	8"	10 lbs.
CT-2	2-1/2"	3"	3"	8"	18 lbs.
CT-20	3"	2-1/2"	2"	8"	20 lbs.
CT-21	3"	2-1/2"	2-1/2"	8"	20 lbs.
CT-22	3"	2-1/2"	3"	8"	20 lbs.
CT-23	3"	3"	2"	8"	20 lbs.
CT-3	3"	3"	3"	8"	18 lbs.
CT-25	3" Male	3"	2"-3"	9-1/2"	19 lbs.
CT-4	4"	3"	3"	7-3/4"	22 lbs.
CT-24	4"	4"	3"	7-3/4"	21 lbs.
CT-6	4"	4"	4"	7-3/4"	18 lbs.
FST	2"	2"	2"	7"	14 lbs.
FST	2-1/2"	2-1/2"	2"	8-1/2"	20 lbs.
DST-31	1-1/2" EUE & 2" NUE or EUE	2" NUE or EUE	2"	6"	6 lbs.



2500 PSI WP

2500 PSI Working Pressure Standard "Yellow" Tees

Model No.	Bottom Thread (Tubing or LP)	Top Thread (Tubing or LP)	Side Outlet (LP)	Height	Weight
YT	2"	2"	2"	5-3/4"	8 lbs.
YT	2-1/2"	2-1/2"	2"	6"	9 lbs.

Note: Pumping Tee Test Pressure > 1.5 X Working Pressure (Male Threads) and 2 X Working Pressure (Female Threads)

* Corrosion-resistant coatings available, contact customer service.